



# 5W30

## Fully synthetic

### PRODUCT DATA SHEET

#### DESCRIPTION

FUELUBE 5W-30 engine oil is a premium formulation featuring a blend of **ESTER** and **PAO (Polyalphaolefin)** base oils. Designed for superior engine protection, it offers exceptional thermal stability and resistance to oxidation, reducing engine wear in high-stress conditions. The ester component provides strong adhesive properties, ensuring an effective oil film even under extreme temperatures.

#### APPLICATION

This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It has a low viscosity formulation that meets the more demanded OEM specifications.

#### FEATURES AND ADVANTAGES

- PERFORMANCE
- PROTECTION
- ENGINE CLEANINESS

#### PRODUCT PERFORMANCE CLAIM

- API SP/ SN/ SN PLUS/ SM/ SL/ SJ/ ILSAC GF-6A
- ACEA A3/B4-21, ACEA C3-21
- BMW Longlife-04
- FORD WSS-M2C947-A/ B1
- MB 229.3/ 226.5
- RENAULT RN0700/ 0710
- Porsche C30, A40
- HONDA HTO-06
- GM dexos1 Gen2, 6094M
- JAGUAR STJLR.51.5122
- Audi Motorsport V31 748 026,
- VW/Audi G 052 195 M2, M4, M6
- OPEL GM-LL-B025
- Fiat 9.55535-GH2, S2



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @15°C	ASTM D4052	kg/m <sup>3</sup>	861.2
Kinematic Viscosity @40°C	ASTM D7042	mm <sup>2</sup> /s	84.96
Kinematic Viscosity @100°C	ASTM D7042	mm <sup>2</sup> /s	13.643
Viscosity index	ASTM D2270	-	164.14
Pour point	ASTM D97	°C	-40
Flash point	IP 523	°C	220

**\*VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

#### HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

